

## :: ZELLAAN CASTING COMPOUND

### *Description:*

Is a harmless and odourless acrylate in powder form for the manufacture of porcelain imitations. It is suitable for indoor and outdoor use and is waterproof. Available in 1 kg, 5 kg, 10 kg and 25 kg packs.

### *Toepassing:*

Afgietingen van stukken en voorwerpen met een porseleinen structuur en uiterlijk. Droogt sneller dan plaster of gips en is duidelijk harder. Kan ingekleurd worden met poederpigmenten.

### *Data on delivery:*

Color:	white
Viscosity:	not applicable
Mass density:	approx. 2,6 gr/cm <sup>3</sup>
Shelf life:	12 months in closed packaging
Consistency:	powder

### *Technical data:*

Consumption:	3,3 kg powder/1 litre water (1 dm <sup>3</sup> cured mixture = 1850 gr)
Shore:	not applicable

### *Application:*

The mixing ratio is 3.3 parts powder to 1 part water by weight. Add the powder to the water while mixing well. Pour the mixture into the silicone or latex mould. It is possible to pour several layers on top of each other when zellaan has not yet hardened. Demouldable after 30 minutes. Zellaan cannot be tumbled.

### *Safety:*

Cleaning agent for tools: water and soap.  
Is not a hazardous material.