

:: BESA POL SATIN 1K LACQUER

Description:

Is a 1 component fast drying satin gloss varnish with good salt water resistant properties, based on urethane-alkyd resin with UV filter that can be easily applied with a brush. This varnish does not form runners, levels well, is hard and yet elastic. The lacquer has a fire class M1 (homologation according to UNE23727-90 tested according to UNE 23721-90).

Available in 1 litre and 5 litre packs.

Application:

Suitable as a finishing coat on new and already painted wood inside and outside, above the waterline. Is further recommended for the protection of metal and GRP substrates, both inside and outside.

Data on delivery:

Color:	transparent / according to RAL 80-90
Viscosity:	KU (Stormer)
Mass density:	approx. 0.96 - 1.22 gr/cm ³
Shelf life:	24 months in closed packaging
Consistency:	liquid

Technical data:

Consumption:	12-13 m ² /litre
Shore:	not applicable

Processing:

Always ensure that the surface is clean, dry and free from grease. Best results are achieved with a flat brush. Minimum application temperature: 5 °C. Do not apply in direct sunlight or on warm surfaces. For porous substrates use primer G4-extra.

Besa pol 1 K is dust-dry after 1 hour and tack-free after 5-6 hours. Recommended waiting time between coats is 24 hours.

Before spraying you can dilute the lacquer 5-10% with SL thinner 1K.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact.

Cleaning agent for tools: SL thinner 1K