

## ::: EPOXY FIX MIX REPAIR KIT

### *Description:*

Is a 2 component epoxy resin for universal applications, which can be processed in combination with glass fabric tape. The resin is completely colourless and fast curing. Has a good UV-resistance and is suitable for both private and industrial use. Simple 1:1 mixing ratio. Cures without sticking. Resistant to seawater, oil, petrol and diluted acids and lyes. Is electrically insulating. Available in handy tubes of 25 ml.

### *Application:*

Ideal resin for various applications e.g. on wood, metal, plastics, leather, rubber, glass, aluminium, ABS, polystyrene, GRP, stone, concrete, etc. Temperature resistant constantly against 100°C and max. 180°C.

### *Data on delivery:*

	<u>A-Comp</u>	<u>B-Comp</u>
Color:	yellowish colourless	Yellowish colourless
Viscosity:	20,000 mPas	20,000 mPas
Mass density:	approx. 1,14 gr/cm <sup>3</sup>	approx. 1.14 g/cm <sup>3</sup>
Shelf life:	12 months in closed packaging	12 months in closed packaging
Consistency:	liquid/ thixotropic	liquid/thixotropic

### *Technical data: (A + B)*

Consumption: Depending on application  
Shore: not applicable

### *Processing:*

Always ensure a dry, rough and grease-free surface. Mix the two components in a 1/1 weight ratio. Potlife: 5 minutes at 20°C. Hard after 4 hours and fully hardened after 24 hours at 23°C. Apply with a spatula at a minimum temperature of 5°C.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).