

:: EPOXY RESIN CLEAR FLEX A+B

Description:

Is a 2 component solvent-free, odourless and crystal-clear elastic casting resin based on epoxy. Suitable for casting in larger volumes. Available in 1kg, 5kg and 30kg sets A+B.

Application:

Casting of crystal-clear strips with increased elasticity, e.g. fittings for LED lights. It is UV-resistant and can be coloured with PU pigments or epoxy pigments.

Data on delivery:A-comp.B-comp.Color:colourlesscolourlessViscosity:450 mPas20 mPasMass density:approx. 1.0 gr/cm³approx. 1.0 gr/cm²

Mass density: approx. 1,0 gr/cm³ approx. 1,01 gr/cm³ Shelf life: 12 months

Shelf life: 12 months
Consistency: liquid liquid

Technical data:

Consumption: Depending on application

Shore: D40 A85

Processing:

Mix both components in a 100:45 ratio by weight. Potlife: 240 min. with thicker layers. Thin layers react even slower. Dry after 48 hours at a temperature of 23°C. Fully cured after 7 days. Always make up quantities according to the processing time.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).