

**::: EPOXY THINNER SEALINE**

**Description:**

Xylene-based solvent for thinning epoxy. Available in 1lt pack.

**Application:**

As a thinner and cleaner for epoxy primers and epoxy resins.

**Data on delivery:**

Color:	colourless
Viscosity:	80 mPas
Mass density:	approx. 0.88 gr/cm <sup>3</sup>
Shelf life:	24 months in closed container
Consistency:	liquid

**Technical data:**

Consumption:	Depending on application
Shore:	not applicable

**Processing:**

Can be mixed under the epoxy, depending on the porosity of the surface to be treated and depending on the type of epoxy.

<u>Epoxy Lightprimer 5:1</u>	<u>Brush / Roll</u>	<u>5-25%</u>
	<u>Spray gun</u>	<u>5-50%</u>
<u>Epoxy Anti-corrosion 4:1</u>	<u>Brush / Roll</u>	<u>5-25%</u>
	<u>Spray gun</u>	<u>5-50%</u>
<u>Epoxy resin</u>	<u>Brush / Roll</u>	<u>0-5%</u>

**Note:** The amounts to be added depend on the type of substrate and the application (primer, paint or coating). Please observe the maximum admissible amounts.

**Safety:**

Always provide appropriate protective clothing and gloves. Thinner is irritating to eyes and skin and is flammable. Cleaning agent for tools: water and soap.