

:: FERRO GLASS

Description:

Is a 2 component fibreglass-filled filling putty. Good sandability, low shrinkage and does not stick to the surface. Specifically for deep fillings. Can be applied in any desired thickness. Available in 1,8 kg packing.

Application :

Well sandable filling putty with improved filling and spreading properties. Has a direct adhesion on metal and GRP. Can be finished with fine finishing putty e.g. FEW, Soft or Multi and then with an appropriate paint system.

Data on delivery:

Color:	green
Viscosity:	40,000 mPas
Mass density:	approx. 1.80 gr/cm ³
Shelf life:	6-8 months in closed packaging
Consistency:	paste / thixotrope

Technical data:

Consumption:	depending on layer thickness
Shore:	not applicable

Application:

Substrate must be dry and free from dust and grease. Mix the filler with 2-3% BPO hardener and apply with a spatula.

Potlife: 4-5 min. at 20°C. Minimum processing temperature: 10°C.

Can already be sanded after 20-30 minutes.

After curing, resistant to temperatures up to 80°C.

Note: all polyesters can be slowed down with inhibitor.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety regulations.