

## :: FERRO MULTI

### *Description:*

Is a 2 component universal polyester putty with a filling effect and with a fine finish. Easy to sand with little dust formation when sanding. After curing, you get a completely tack free surface.

Available in packaging of 2 kg and 10 kg.

### *Application:*

Very fine finish for unevenness in metal, polyester, tin-plated and galvanised sheet. The ferro multi has a good adhesion on galvanised steel, aluminium, steel and light metal surfaces. Should be finished with an appropriate paint system.

### *Data on delivery:*

Color:	beige
Viscosity:	40,000 mPas
Mass density:	approx. 1.87 gr/cm <sup>3</sup>
Shelf life:	6 months in closed packaging
Consistency:	paste thixotrope

### *Technical data:*

Consumption:	depending on application
Shore:	not applicable

### *Application:*

Substrate must be dry and free of dust and grease. Mix the polyester with 2-3% BPO hardener and apply this mixture with a spatula. Can already be sanded after 20-30 min.

Potlife: 4-5 min. at 20°C. Processing temperature: min. 10°C.

After curing resistant to temperatures up to 80°C. Maximum layer thickness 5 mm.

Note: all polyesters can be slowed down with inhibitor.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety instructions.