

## ::: POLISH S05 ONE STEP HEAVY CUT & GLOSS

### *Description:*

Is a one-step polishing paste for sanding and shining a surface consisting of polyester, epoxy, polyurethane and other lacquers as well as plexiglass. Contains a fine grain that also removes fine scratches after sanding with P800. Available in 1 kg packaging.

### *Application:*

As a deep cleaner for polyester, epoxy and polyurethane. Can also be used on plexiglass. No additional polishing is required.

### *Data on delivery:*

Color:	white
Viscosity:	20000 mPas
Mass density:	approx. 1.42 gr/cm <sup>3</sup>
Shelf life:	24 months in closed packaging.
Consistency:	paste

### *Technical data:*

Consumption:	depends on the substrate.
Shore:	not applicable
abrasive strength:	9/10
gloss level:	8/10

### *Processing:*

It is best to apply this grinding paste with a polishing pad or lambswool and a polishing machine. Start with a speed of 800-1000 rpm until the paste changes colour and texture. Slowly increase the speed to a maximum of 1800 rpm and apply some extra pressure to the surface. Does not stick or splash. Can also be applied manually. Processing temperature: 15 - 25 °C  
Treat the surface afterwards with SL S5 quick wax or SL S4 Protect wax for a long-lasting protection.

**Tip:** When the hull is waxed, it is advisable to cover the waterline with a wide strip of tape. Wax can worsen the adhesion of new antifouling layers.

### *Safety:*

Always wear suitable gloves and protective clothing. Keep out of reach of children. Cleaning agent for tools: water and soap.