

## :: BESA POL SATIN 1K LACQUER

### **Description:**

Is a 1 component fast drying satin gloss varnish with good salt water resistant properties, based on urethane-alkyd resin with UV filter that can be easily applied with a brush. This varnish does not form runners, levels well, is hard and yet elastic. The lacquer has a fire class M1 (homologation according to UNE23727-90 tested according to UNE 23721-90).

Available in 1 litre and 5 litre packs.

### **Application:**

Suitable as a finishing coat on new and already painted wood inside and outside, above the waterline. Is further recommended for the protection of metal and GRP substrates, both inside and outside.

### **Data on delivery:**

<b>Color:</b>	transparent / according to RAL 80-90
<b>Viscosity:</b>	KU (Stormer)
<b>Mass density:</b>	approx. 0.96 - 1.22 gr/cm <sup>3</sup>
<b>Shelf life:</b>	24 months in closed packaging
<b>Consistency:</b>	liquid

### **Technical data:**

<b>Consumption:</b>	12-13 m <sup>2</sup> /litre
<b>Shore:</b>	not applicable

### **Processing:**

Always ensure that the surface is clean, dry and free from grease. Best results are achieved with a flat brush. Minimum application temperature: 5 °C. Do not apply in direct sunlight or on warm surfaces. For porous substrates use primer G4-extra.

Besa pol 1 K is dust-dry after 1 hour and tack-free after 5-6 hours. Recommended waiting time between coats is 24 hours.

Before spraying you can dilute the lacquer 5-10% with SL thinner 1K.

### **Safety:**

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact.

Cleaning agent for tools: SL thinner 1K