

:: PUTTY FILLER MEDIUM GREY

Description:

2 component very fine finishing putty based on polyester. Very well sandable with little shrinkage and dust formation during sanding. After curing, you get a completely tack free surface. Applicable on polyester (GRP) and metal. Available in 2 kg and 10 kg. (tube)

Application:

Very soft sandable putty with fine finish for unevenness in metal, GRP, wood, concrete or other putties. Can be finished with an appropriate varnish system.

Data on delivery:

| | |
|----------------------|---------------------------------|
| Color: | medium grey |
| Viscosity: | 40,000 mPas |
| Mass density: | approx. 1.87 gr/cm ³ |
| Shelf life: | 6-8 months in closed packaging |
| Consistency: | paste/thixotrope |

Technical data:

| | |
|---------------------|------------------------------|
| Consumption: | depending on layer thickness |
| Shore: | not applicable |

Application:

Substrate must be dry, dust and grease free. Mix the polyester with 2-3% BPO hardener and apply with a spatula.

Potlife: 8-10 min. at 20°C. Can already be sanded after 20-30 min.

Processing temperature: min. 10°C. After curing, resistant to temperatures up to 80°C.

Maximum recommended layer thickness is 5 mm.

Note: all polyesters can be slowed down with inhibitor.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety regulations.