

## ::: BESA POL SATIN 1K PAINT

### *Description:*

Is a 1 component fast drying high gloss varnish with good salt water resistant properties, based on urethane-alkyd resin with UV filter that can be easily applied with a brush. This varnish does not form runners, levels well, is hard and yet elastic. The lacquer has a fire class M1 (homologation according to UNE23727-90 tested according to UNE 23721-90). Available in 1 litre and 5 litre packs.

### *Application:*

Suitable as a finishing coat on new and already painted wood inside and outside, above the waterline. Is further recommended for the protection of metal and GRP substrates, both inside and outside.

### *Data on delivery:*

Color:	transparent / according to RAL
Viscosity:	80-90 KU (Stormer)
Mass density:	approx. 0.96 - 1.22 gr/cm <sup>3</sup>
Shelf life:	24 months in closed packaging
Consistency:	liquid

### *Technical data:*

Consumption:	12-13 m <sup>2</sup> /litre
Shore:	not applicable

### *Processing:*

Always ensure that the surface is clean, dry and free from grease. Best results are achieved with a flat brush. Minimum application temperature: 5 °C. Do not apply in direct sunlight or on warm surfaces.

For porous substrates use primer G4-extra.

Besa pol 1 K is dust-dry after 1 hour and tack-free after 5-6 hours. Recommended waiting time between coats is 24 hours.

For spraying you can dilute 0-10% with SL thinner 1K.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact.

Cleaning agent for tools: SL thinner 1K