

## :: SUPER EPOXY GLUE

### *Description:*

Is a 2-component epoxy adhesive for universal applications. The adhesive is completely colourless and fast curing. Very good UV-resistance and suitable for both private and industrial use. Simple mixing ratio. Cures without sticking. Resistant to seawater, oil, petrol and diluted acids and bases. Is electrically insulating. Available in handy tubes of 30 gr.

### *Application:*

Ideal instant adhesive for various applications e.g. on wood, metal, plastics, leather, rubber, glass, aluminium, ABS, polystyrene, GRP, stone, concrete, etc.  
Temperature resistant constant against 100°C and max. 180°C.

### *Data on delivery:*

	<u>A-Comp</u>	<u>B-Comp</u>
Color:	colourless	colourless
Viscosity:	20,000 mPas	20,000 mPas
Mass density:	approx. 1.15 gr/cm <sup>3</sup>	approx. 1,13 gr/cm <sup>3</sup>
Shelf life:	12 months in closed packaging	12 months in closed packaging
Consistency:	liquid/thixotrope	liquid/thixotrope

### *Technical data: (A + B)*

Consumption:	Depending on application
Shore:	not applicable

### *Processing:*

Mix the two components in a 1/1 weight ratio. Potlife: 5-10 min. at 20°C. Fully cured after 24 hours at 23°C. Apply with a spatula at a minimum temperature of 5°C. Always ensure a dry, rough and grease-free surface.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).