

## :: FERRO SPRAY

### *Description:*

Is a 2 component polyester spray putty with a filling effect, very good sandability and little dust formation when sanding.

Available in 1,5 kg packaging.

### *Field of application:*

As a sprayable finishing putty after a polyester repair or for on wood, metal, concrete or GRP. Smooth finish and soft sandable. Can be applied without primer on polyester and can be further finished with an appropriate paint system.

### *Data on delivery:*

Color:	grey
Viscosity:	14,000 mPas
Mass density:	approx. 1.7 gr/cm <sup>3</sup>
Shelf life:	6-8 months in closed packaging
Consistency:	liquid

### *Technical data:*

Consumption:	ca. 600gr/m <sup>2</sup>
Shore:	not applicable

### *Application:*

Substrate must be dry, dust- and grease free. Mix the resin with 3.5% CHP hardener and process this mixture within 15-20 min. at 20°C. Can already be sanded after 120-180 min. To be diluted 2.5% with Spray Thinner .

At a spraying pressure of 3-4 bar and with a spray nozzle of: 2-3.5 mm.

After curing, resistant to temperatures up to 80°C.

Note: all polyesters can be slowed down with inhibitor.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety regulations.