

## :: G4 PRIMER

### *Description:*

1 component solvent-based PU resin that reacts to air humidity. G4 PRIMER is a limited UV-resistant (yellowing with time), but extremely scratch-resistant primer that is solvent and chemical resistant. Can also be used as an adhesive and protective layer. Available in 0.5 lt, 1 lt, 2.5 lt, 5 lt, 10 lt, 20 lt and 200 lt containers.

### *Application:*

As a primer for all cold-curing plastics (except epoxy) and for most other paints etc.

### *Data on delivery:*

Color:	brownish transparent 150
Viscosity:	mPas
Mass density:	approx. 0.95 gr/cm <sup>3</sup>
Shelf life:	2 years in closed packaging
Consistency:	thin liquid

### *Technical data:*

Consumption:	2 - 6 m <sup>2</sup> per litre depending on the porosity of the substrate
Shore:	not applicable

### *Processing:*

Always make sure the surface is as dry and grease-free as possible and apply G4 PRIMER with a brush or roller. Does not need to be diluted, but can be diluted up to 50% with PU thinner for impregnating walls. Can be applied to damp substrates, but this will make it harder for the G4 PRIMER to penetrate the substrate. Dust-free after 1 hour. Can be painted over as soon as surface is tack free. Max. waiting time for overcoating is 48 hours. Waiting time between coats 2-8 hours.

Overpaintable with traditional paints. Especially for floors, we recommend our Estovoss floor paint.

Attention: Once packages have been opened, always close them airtight to prevent further hardening in the tin. Pour any surplus into a small container so that no air can enter.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. The use of a carbon filter mask type A2 is recommended.

Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone)

Always ensure adequate ventilation.