

::: POLISH S0 FAST CUT & MEDIUM GLOSS

Description:

Is a highly effective polishing paste for gel coats and industrial polyester paints and polyurethane paints that do not contain silicones. Contains a fine grain that also removes fine scratches after sanding with P800. Available in 1 kg packaging.

Application:

As a universal polishing paste for polyester, epoxy and polyurethane. Thanks to its composition, heat generation is avoided during work.

Data on delivery:

Color:	white
Viscosity:	20000 mPas
Mass density:	approx. 1.49 gr/cm ³
Shelf life:	24 months in closed packaging.
Consistency:	paste

Technical data:

Consumption:	depends on the substrate.
Shore:	not applicable
Abrasiveness:	8/10
Gloss level:	6/10

Processing:

It is best to apply this grinding paste with a polishing pad or lambswool and a polishing machine. Start with a speed of 800-1000 rpm until the paste changes colour and texture. Slowly increase the speed to a maximum of 1800 rpm and apply some extra pressure to the surface. Does not stick or splash.

Can also be applied manually. Processing temperature: 15 - 25 °C

For an even higher gloss level, you can refinish the surface with the SL S1 one-step cut and high gloss. Then treat the surface with the SL S5 quick wax or SL S4 Protect wax for a long-time protection.

Tip: When the hull is waxed, it is advisable to cover the waterline with a wide strip of tape. Wax can worsen the adhesion of new antifouling layers.

Safety:

Always wear suitable gloves and protective clothing. Keep out of reach of children. Cleaning agent for tools: water and soap.