

## ::: PUR INMOULD COATING SLOW BASE A+B

### *Description:*

Is a 2-component, paintable polyurethane inmould coating with low odour development and good chemical properties. Available in 300 g and 1.2 kg containers.

### *Application:*

Can be used as a gelcoat (inmould coating) to be continued with another polyurethane. This product can be applied in 2 mm. without dripping. Can be coloured with 1-3 % PUR colourant.

### *Data on delivery:*

Color:	<u>A-comp.</u>	<u>B-comp.</u>
Viscosity:	yellowish	yellowish
Mass density:	8,000 MPa	650 MPa
Shelf life:	approximately 1,05 gr/cm <sup>3</sup>	approximately 1,22 gr/cm <sup>3</sup>
Consistency:	6 months in closed packaging thixotropic	6 months in closed container liquid

### *Technical data:*

Consumption:	depending on application
Shore:	+/- A 40

### *Processing:*

Always ensure that the surface is as dry as possible. Mix the individual components well before use. Mixing ratio 100/20 by weight. Processing time: + 60 min. Tack-free (1.5 mm) after 6 hours. De-formable: depending on layer thickness 1 - 2 hours. Can already be worked over within 2 - 4 hours with another polyurethane. This gives a better adhesion between the layers.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. The use of a carbon filter mask type A2 is recommended. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).