

## ::: CAST RESIN GTS

### **Description:**

Is a 2-component, pre-accelerated transparent polyester casting resin with very good UV resistance. Available in 5, 20 and 220 kg and ibc (1060 kg) packaging.

### **Application:**

For casting in a crystal-clear polyester.

E.g. for casting fragile objects, wedding bouquets, photos, shells, etc.

### **Data on delivery:**

Color:	Light blue (colourless after curing)
Viscosity:	600-800 mPas
Mass density:	approx. 1.13 gr/cm <sup>3</sup>
Shelf life:	6 months in closed packaging
Consistency:	liquid

### **Technical data:**

Consumption:	depending on application
Shore:	D 50

### **Processing:**

Mix the resin with 1-3% Mekk hardener (depending on the volume to be poured) and pour the resin into the mould without bubbles. Potlife: 30 min. at 20°C. Always make small quantities in proportion to the potlife. When pouring large volumes of resin, add max. 0.5-1% hardener.

**Tip:** Use our Trennspray as release agent and YC High Gloss Finish as polishing agent.

**Caution:** Do not pour in any metal objects, as this may cause a reaction with the resin. **Nota:** alle polyesters zijn te vertragen met inhibitor.

### **Safety:**

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: Cleaner M (environmentally friendly alternative to acetone)

This product contains styrene and must therefore be handled in accordance with the safety regulations.