

::: UNIVERSAL HYBRID TRANSPARANT

Description:

Is an elastic grouting resin based on 1 component MS polymer. Is highly elastic after curing and not overpaintable. Available in transparent. Available in cartridges of 290 ml.

Application:

For bonding and/or filling almost any substrate. For bonding silicone rubbers, sealings on different surfaces like GRP, aluminium, steel, glass, ceramics and wood. Very good mechanical properties and resistant to diluted acids and alkalis. Temperature resistant between -40°C and 60°C.

Data on delivery:

Color:	transparent
Viscosity:	160,000 MPa approx.
Mass density:	1,03 gr/cm ³
Shelf life:	6 months
Consistency:	paste

Technical data:

Consumption:	depending on application
Shore:	

Processing:

Always ensure that the surface is as dry and grease-free as possible. Apply the glue with a spatula and then press the 2 pieces to be glued together. Smooth with a finger moistened with soap or water. Best processed at a temperature between 15-25°C. Skin formation after 10 minutes at 20°C. Dust dry after 10 min. Fully cured after 24 hours at 4 mm thickness.

Caution: Do not use on PE, PP, PTFE and bituminous surfaces!

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).