

::: EPOXY FIBREGLASS FILLER GREY A+B

Description:

Is a 2 component solvent-free fibre reinforced putty based on epoxy. This putty can be applied in layers up to 10 mm without shrinking. Available in 750 kg and 7.5 kg containers.

Application:

Excellent for repairing damage above and below the waterline on steel, hardwood, polyester and concrete. Excellent for osmosis repairs on polyester boats.

Aluminium, steel and GRP surfaces should be pre-treated with Epoxy Light Primer.

<i>Data on delivery:</i>	<u>A-comp</u>	<u>B-comp</u>
Color:	white	light grey
Viscosity:	80000 mPas	80000 mPas
Mass density:	1.55 g/cm ³	1.55 g/cm ³
Shelf life:	24 months in closed packaging	12 months in closed packaging
Consistency:	paste	paste

Technical data:

Consumption: 3.7 m² at 200 micron layer thickness

Shore: Not applicable

Processing:

The surface must be clean, dry and grease-free. Mix both components in a 2/1 volume ratio or 100:50 by weight and process within 50 min at 20°C. Apply with a spatula. Depending on the surface and quality, sand or use light primer. Can be sanded after 16 hours at 20°C. Never apply below 10°C.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).