

## ::: PUR LACQUER 1K ENAMEL

### *Description:*

Is a 1 component fast drying high gloss paint with good salt water resistant properties based on urethane-alkyd resin with UV filter.  
Available in 750 ml packaging.

### *Application:*

Suitable as a finishing coat on new and already painted wood inside and outside, above the waterline. Can also be applied on gfk or steel surfaces.

### *Data on delivery:*

Color:	White, ecru, blue (ask for other colours) 800
Viscosity:	mPas
Mass density:	approx. 1.00 gr/cm <sup>3</sup>
Shelf life:	24 months in closed packaging
Consistency:	liquid

### *Technical data:*

Consumption:	approx. 15 m <sup>2</sup> /litre
Shore:	not applicable

### *Processing:*

Always ensure that the surface is clean, dry and free from grease. Best results are achieved with a flat brush. Minimum application temperature: 5 °C. Do not apply in direct sunlight or on warm surfaces. Thin if necessary with 10% SL Yacht enamel thinner. Covering in 1-2 layers. Waiting time between layers: minimum 16 hours. Hand-dry after 3 hours. Rain resistant after 6 hours.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact.  
Cleaning agent for tools: SL yacht enamel thinner