

::: PUR INMOULD COATING FAST BASE A+B

Description:

Is a 2-component, paintable polyurethane inmould coating with low odour development and good chemical properties. Available in 600 gr packaging.

Application:

Can be used as a gelcoat (inmould coating) to be continued with another polyurethane. This product can be applied in 2 mm. without dripping. Can be coloured with 1-3 % PUR colourant.

Data on delivery:

	<u>A-comp.</u>	<u>B-comp.</u>
Color:	yellowish	yellowish
Viscosity:	8,000 MPa	650 MPa
Mass density:	approximately 1,05 gr/cm ³	approximately 1,22 gr/cm ³
Shelf life:	6 months in closed packaging	6 months in closed packaging
Consistency:	thixotropic	liquid

Technical data:

Consumption: depending on application
Shore: +/- A 40

Processing:

Always ensure that the surface is as dry as possible. Mix the individual components well before use. Mixing ratio 100/20 by weight. Processing time: Approx. 10 min. Tack-free (1.5 mm.) after 6 hours. Deformable: depending on layer thickness 1 - 2 hours. Can be worked over with another polyurethane within 30 to 40 minutes. This gives a better adhesion between the layers.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. The use of a carbon filter mask type A2 is recommended. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).