

::: EPOXY THINNER SEALINE

Description:

Xylene-based solvent for thinning epoxy. Available in 1lt pack.

Application:

As a thinner and cleaner for epoxy primers and epoxy resins.

Data on delivery:

| | |
|---------------|---------------------------------|
| Color: | colourless |
| Viscosity: | 80 mPas |
| Mass density: | approx. 0.88 gr/cm ³ |
| Shelf life: | 24 months in closed container |
| Consistency: | liquid |

Technical data:

| | |
|--------------|--------------------------|
| Consumption: | Depending on application |
| Shore: | not applicable |

Processing:

Can be mixed under the epoxy, depending on the porosity of the surface to be treated and depending on the type of epoxy.

| | | |
|---------------------------------|---------------------|--------------|
| <u>Epoxy Lightprimer 5:1</u> | <u>Brush / Roll</u> | <u>5-25%</u> |
| | <u>Spray gun</u> | <u>5-50%</u> |
| <u>Epoxy Anti-corrosion 4:1</u> | <u>Brush / Roll</u> | <u>5-25%</u> |
| | <u>Spray gun</u> | <u>5-50%</u> |
| <u>Epoxy resin</u> | <u>Brush / Roll</u> | <u>0-5%</u> |
| | | |

Note: The amounts to be added depend on the type of substrate and the application (primer, paint or coating). Please observe the maximum admissible amounts.

Safety:

Always provide appropriate protective clothing and gloves. Thinner is irritating to eyes and skin and is flammable. Cleaning agent for tools: water and soap.