

:: FEW

Description:

2 component very fine finishing putty based on polyester. Very well sandable with little shrinkage and dust formation during sanding. After curing, you get a completely tack free surface. Applicable on polyester (GRP), wood, concrete and metal.

Available in 3 kg (cartridge) and 10 kg (cartridge).

Application:

Very soft sandable putty with fine finish for unevenness in metal, GRP, wood, concrete or other putties. Can be finished with an appropriate varnish system.

Data on delivery:

Color:	white
Viscosity:	40,000 mPas
Mass density:	approx. 1.87 gr/cm ³
Shelf life:	6-8 months in closed packaging
Consistency:	paste/thixotrope

Technical data:

Consumption:	depending on layer thickness
Shore:	not applicable

Application:

Substrate must be dry, dust and grease free. Mix the polyester with 2-3% BPO hardener and apply with a spatula. Potlife: 4-5 min. at 20°C. Can already be sanded after 20-30 min.

Processing temperature: min. 10°C. After curing, resistant to temperatures up to 80°C.

Maximum recommended layer thickness is 5 mm.

Note: all polyesters can be slowed down with inhibitor.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety regulations.