

::: ACRYLIC 1K FILLER

Description:

Acrylic filler putty in a multifunctional, 1 component acrylic-based repair putty. It is widely applicable for and directed towards painting jobs. The putty is shrinkage-free, pore-free and can be painted over without much reworking. The adhesion on stone, concrete, plaster, wood and metal is perfect. Available in 1000 gr packaging.

Application:

- Levelling small and medium-sized unevennesses on the above substrates Improving
- and smoothing minor paintwork damage
- Creation of an improved fine and less porous surface Sealing of pores and
- irregularities
- Contouring in model making or repairs
- Filling out of cracks and weathered spots in wood such as on windows and doors

Data on delivery:

	<u>1-Comp</u>
Colour :	Matt white
Specific gravity:	approx. 1,9 g/l cm ³
Storage life : Processing	12 months in closed package
temperature : Drying	Between 10 and 20°C (not below 7°C)
time:	Sandable after 1 to 2 hours at 20°C
	Completely dry after 24
Cleaning	Water (clean tools immediately)

Application:

The surface must be clean and free of grease and loose particles. With metal, always apply an oxidation protector first (e.g. G4). Painted surfaces must be sanded first. Knead the tube well, and the putty is ready for use. Apply with spatula or putty knife. After 1 to 2 hours, the surface can be sanded, a new layer applied or it can be repainted.

Safety:

Always provide appropriate protective clothing and gloves. Always consult the safety data sheet. The processing of these products is based on our experience in normal circumstances. The products may react differently under different conditions and surfaces.