

:: FILL-21

Description:

Is a 2-component polyester-based filling putty with good sandability and universal in application. Both to fill and to finish. After curing, you get an tack-free surface. Available in packaging of 2 kg.

Field of application:

Well sandable and easy to apply filling putty for wood, GRP, concrete, metal or galvanised sheet and aluminium (sand well). As finishing of damaged polyester or car body parts. Can be finished with an appropriate paint system.

Data on delivery:

Color:	beige
Viscosity:	40000 mPas
Mass density:	approx. 1.87 gr/cm ³
Shelf life:	6-8 months in closed packaging
Consistency:	paste / thixotrope

Technical data:

Consumption:	depending on application
Shore:	not applicable

Application:

Substrate must be dry and free from grease. Mix the filler with 2-3% BPO hardener and apply this mixture with a spatula. Can already be sanded after 20-30 minutes.

Processing time: 3-4 min. at 20°C. Minimum application temperature: 10°C. After curing, resistant to temperatures up to 80°C. Maximum recommended layer thickness is 5 mm.

Note: All polyesters can be slowed down with inhibitor.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety instructions.