

:: CLEAR TEAK OIL

Description:

Is a low-viscosity oil with a very high penetration rate based on alkyd resin. Teak oil is resistant to water, does not leave a greasy film. Available in 250 ml packaging.

Application:

Suitable for impregnating exotic woods such as teak, mahogany, padouk, iroko, azobe, ... for inside and outside on the boat. Does not contain silicone oil.

Attention: is not suitable for already painted surfaces.

Data on delivery:

Color:	colourless
Viscosity:	200 MPa
Mass density:	ca 0,80 gr/cm ³
Shelf life:	5 years in closed packaging
Consistency:	liquid

Technical data:

Consumption:	+ - 10 m ² /liter
Shore:	not applicable

Application:

First clean the surface to be treated and allow to dry thoroughly. Apply a first layer by brush or roller. Do not let the first layer dry completely but apply "wet-on-wet". Waiting time between coats is +/- 30 minutes. Drying time at 20°C, 5 hours. Fully cured after 3 days.

Remove excess oil with a cloth before drying.

Attention: Self combustion of the cloth is possible, therefore remove the cloth carefully after use.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: thinner 08230 or cleaner M (environmentally friendly substitute for acetone).