

## **:: PUTTY FILLER DARK GREY**

### *Description:*

2 component very fine finishing putty based on polyester. Very well sandable with little shrinkage and dust formation during sanding. After curing, you get a completely tack free surface. Applicable on polyester (GRP) and metal. Available in 2 kg and 9,7 kg (tube).

### *Application:*

Very soft sandable putty with fine finish for unevenness in metal, GRP, wood, concrete or other putties. Can be finished with an appropriate varnish system.

### *Data on delivery:*

Color:	Dark grey
Viscosity:	40,000 mPas
Mass density:	approx. 1.87 gr/cm <sup>3</sup>
Shelf life:	6-8 months in closed packaging
Consistency:	paste/thixotrope

### *Technical data:*

Consumption:	depending on layer thickness
Shore:	not applicable

### *Application:*

Substrate must be dry, dust and grease free. Mix the polyester with 2-3% BPO hardener and apply with a spatula. Potlife: 8-10 min. at 20°C. Can already be sanded after 20-30 min.

Processing temperature: min. 10°C. After curing, resistant to temperatures up to 80°C.

Maximum recommended layer thickness is 5 mm.

Note: all polyesters can be slowed down with inhibitor.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety regulations.