

:: V11 + BPO

Description:

Is a 2-component glass fibre filled polyester putty. Ideal as reinforcement or filling of rust affected metal sheets. Bonding of wood, polyester and stone.

Can be applied in any desired thickness. Available in 700 gr and 1,3 kg, 5,6 lt (cartridges).

Application:

Filling and strengthening metal, wood, stone and polyester. For quick bonding of metal, polyester and wood. Can be finished with FEW finishing putty and with an appropriate paint system.

Data on delivery:

Color:	yellow-brown
Viscosity:	40,000 mPas
Mass density:	approx. 1.30 gr/cm ³
Shelf life:	6 - 8 months in closed container
Consistency:	paste

Technical data:

Consumption:	depending on layer thickness
Shore:	not applicable

Application:

The substrate must be dry and free from dust and grease. Mix the paste with 2-3% BPO hardener and apply with a spatula. Potlife: 5 min. at 20°C. Processing temperature: 5-20°C. Can be sanded off after 20 minutes. Remains slightly sticky on the surface for improved adhesion of the finishing putty. After curing, resistant to temperatures up to 80°C.

Note: all polyesters can be slowed down with inhibitor.

Safety:

Always wear suitable protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).

This product contains styrene and must therefore be handled in accordance with the safety regulations.