

## :: CLEAR YACHT VARNISH 1K

### *Description:*

Is a 1 component fast drying high gloss paint with good salt water resistant properties based on urethane-alkyd resin with UV filter.  
Available in 750 ml packaging.

### *Application:*

Suitable as a finishing coat on new and already painted wood inside and outside, above the waterline.

### *Data on delivery:*

Color:	transparent
Viscosity:	800 mPas
Mass density:	approx. 0.91 gr/cm <sup>3</sup>
Shelf life:	24 months in closed packaging
Consistency:	liquid

### *Technical data:*

Consumption:	ca. 12-13 m <sup>2</sup> /liter
Shore:	not applicable

### *Processing:*

Always ensure that the surface is clean, dry and free from grease. Best results are achieved with a flat brush. Minimum application temperature: 5 °C. Do not apply in direct sunlight or on warm surfaces. When renewing old varnish, it is best to dilute the first layer by 10-20% with SL Yacht enamel thinner. For new wood thinning the first coat approximately 40% with SL Yacht enamel thinner, the second coat 10-20%. The following layers do not need to be thinned.

Apply in 1-3 layers for already treated surfaces, 4-5 layers for new wood.

Waiting time between coats: minimum 16 hours. Hand-dry after 3 hours. Rain resistant after 6 hours.

### *Safety:*

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact.

Cleaning agent for tools: SL yacht enamel thinner or cleaner M (environmentally friendly substitute for acetone).