

::: CAR KS 50 SEALANT

Description:

Is a 1-component synthetic rubber-based sealant for sealing sheets and seams on bodywork. The fast-drying paste gives an elastic, heat and cold resistant layer (-25°C to +80°C), which can be painted over. (-25°C to +80°C), which can be painted over. Available in 1,000 ml packaging.

Application:

Suitable for seam and joint sealing of welds and spot seams. Especially for bodywork parts such as mudguards and spoilers. Resists water and mineral oils well and has anti-corrosion properties.

Data on delivery:

Color:	grey
Viscosity:	7000 mPas
Mass density:	approx. 1,2 gr/cm ³
Shelf life:	6 months in closed packaging
Consistency:	paste

Technical data:

Consumption:	1.2 kg/m ²
Shore:	not applicable

Processing:

Always ensure a dry and grease-free surface. Apply the paste with a spatula in the thinnest possible layer. Apply the paste with a brush to bare, primed or varnished surfaces. The paste does not drip off during application. Do not apply below 15°C. Do not apply to engine, exhaust and functional parts such as axles and shock absorbers.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone)