

:: HIGH GLOSS FINISH POLYGLANZ

Description:

Is a silicone-free polishing paste for making a surface consisting of polyester, epoxy, polyurethane and other lacquers and even plexiglass shine and lustre. Very suitable as final treatment after use of e.g. oxalic acid. Contains a very fine grain that also removes fine scratches. First clean the surface with Yacht cleaner or sealine degreaser.

Available in 200 g and 500 g packaging.

Application:

As a deep cleaner for polyester, epoxy and polyurethane. Can also be used on plexiglass. A wax layer remains on the surface.

Data on delivery:

Color:	white
Viscosity:	20000 mPas
Mass density:	approx. 1,0
Shelf life:	gr/cm ³
Consistency:	unlimited

Technical data:

Consumption:	50 gr/m ²
Shore:	not applicable

Processing:

Always ensure a dry and grease-free surface. Apply the paste with a soft cloth in circular movements and polish thoroughly with light pressure. Remove paste residues with a cloth and let the surfaces shine. Repeat the process if necessary. Can be machined, but beware of too high a speed (max. 800 TPM with a polishing fleece - diameter 13 cm). Continuously change the position of the fleece so that the surface does not become too hot. Can be thinned with white spirit or turpentine if necessary. Do not let the high gloss finish dry out.

Tip: When the hull is waxed, it is advisable to cover the waterline with a wide strip of tape. Wax can worsen the adhesion of new antifouling layers.

Safety:

Always wear suitable gloves and protective clothing. Keep out of reach of children. Cleaning agent for tools: water and soap.