

::: Cleaning Agent MP-GP

Description:

Is a powerful, liquid and fast-acting paint remover for removing various paints, varnishes and adhesives. Available in 1l, 5l, 10l, 25l, 210l and 1000l

Application:

For removing paints, varnishes and glues.

Data on delivery:

| | |
|---------------|---------------------------------|
| Color: | colourless |
| Viscosity: | 1 Mpa at 20° C |
| Odour: | characteristic |
| Mass density: | approx. 1.028 g/cm ³ |
| Ph: | > 12 |
| Flash point: | 8° C |
| Shelf life: | 12 months in closed packaging |
| Consistency: | liquid |

Technical data:

| | |
|--------------|--------------------------|
| Consumption: | depending on application |
| Shore: | not applicable |

Application:

The soaking time depends on the nature (type of paint, varnish or glue) and extent (layer thickness) of the paint, varnish or glue to be removed.

Immerse the part or object to be treated in a bath of undiluted product.

For glues: Leave it to soak until the glue becomes soft and remove the loosened glue with a spatula. Then wipe the object again with a cloth (moistened with Cleaning Agent MP - GP) and let it dry.

For varnishes: Allow to soak in until the paint or varnish detaches from the part or object and sinks to the bottom of the bath. Then rinse with clean water, clean product or an alkaline solution and dry or allow to dry.

If the product is applied, we recommend that you rinse the unit thoroughly after use to minimise seal deterioration.

Hostafilon seals are the most resistant to degradation.

Safety:

Keep out of reach of children. No special precautions need to be taken but in case of prolonged contact wear chemically resistant gloves.

Cleaning agent for tools: soap and water.