

:: EPOXY LIGHTWEIGHT FILLER WHITE A+B

Description:

Is a 2 component solvent-free lightweight putty based on epoxy (0.8 kg/litre.) This putty can be applied in layer thicknesses up to 10 mm without shrinking.

Available in 750 ml and 7.5 kg packaging.

Application:

Excellent for repairing damages above and below the waterline of steel, hardwood, polyester and ferro-cement. Also suitable for osmosis repairs on polyester boats. Aluminium surfaces must first be treated with epoxy light primer.

Data on delivery:

	<u>A-comp</u>	<u>B-comp</u>
Color:	white	light grey
Viscosity:	80000 mPas	80000 mPas
Mass density:	0.72 g/cm ³	0.75 g/cm ³
Shelf life:	24 months in closed packaging	24 months in closed packaging
Consistency:	paste	paste

Technical data:

Consumption:	6 m ² / kg at 200 micron layer thickness
Shore:	Not applicable

Processing:

The surface must be clean, dry and grease-free. Mix both components in a 1/1 volume ratio or a 100:100 weight ratio and process within 50 min at 20°C. Apply with a spatula. Depending on the substrate and quality, sanding or blasting should be carried out first. Can be sanded after 24 hours (20°C.) Can be loaded with water after 48 hours. Never apply below 10°C.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged skin contact. Cleaning agent for tools: cleaner M (environmentally friendly substitute for acetone).