

::: GELCOAT REPAIR FILLER DRY FAST

Description:

Is a white 2-component, filled and pre-accelerated paste based on polyester resin with a virtually shrinkage-free curing. Available in 250 gr packaging.

Application:

Finds its application in boat building. For fixing, filling and repairing gelcoat above the waterline. For fast and durable repairs on polyester. Do not apply to 1-component paints or surfaces that could be affected by solvents.

Data on delivery:

Color:	white (ral 9010 & 9001)
Viscosity:	20000 mPas
Mass density:	1,35 gr/cm ³
Shelf life:	12 months in closed packaging
Consistency:	paste/thixotrope

Technical data:

Consumption:	0,5 - 1 kg/m ²
Shore:	not applicable

Application:

The surface must always be dry and free of dust and grease. Mix the polyester with 2% hardener and apply this mixture with a rubber spatula. Can already be loaded after 2-3 hours. Potlife: 10-20 min at 20°C. Always make small quantities in proportion to the potlife. Processing temperature: 15-20°C. Apply a maximum of 0.4 -1.0 mm per layer. If necessary, sand between layers to improve the adhesion.

Attention: Do not add more hardener than indicated.

Safety:

Always provide appropriate protective clothing and gloves. Avoid prolonged contact with the skin. Cleaning agent for tools: cleaner M or acetone and for hands: hand cleaner Slig (soap Stockhausen). This product contains styrene and must therefore be handled in accordance with the safety regulations.